

AP 103

FAST DRY ASPHALT PRIMER Data Sheet



COMPLIANCE: Exceeds performance requirements of ASTM D 41. MIAMI-DADE APPROVED. ASBESTOS FREE.

DESCRIPTION: APOC® 103 Fast Dry Asphalt Primer is a professional grade primer formulated with a high penetrating solvent and select asphalt. It is designed to promote superior adhesion of roofing materials. APOC® 103 can be used to prime newly laid concrete or cement decks, gypsum, masonry thermal insulation and weathered roofing prior to applying built-up roofing. APOC® 103 can also be applied to weathered roofing prior to application of black or reflective coatings. Allow primer to cure 30 days prior to application of reflective coatings.

PREPARATION: All surfaces must have proper drainage and be clean, dry and free of surface rust and any other foreign matter. Repair all problem areas with an approved APOC® Cement. MIX THOROUGHLY. DO NOT HEAT OR THIN. DO NOT APPLY IF RAIN IS EXPECTED WITHIN 24 HOURS.

FOR BEST RESULTS: Apply on clear sunny day when surface temperatures are between 35° and 120° F. In colder weather product should be stored in heated room (65° to 80°F) at least 24 hours prior to application.

APPLICATION: For exterior use only. Protective clothing and eyewear should be used during application of these products. Apply with professional airless sprayer, brush or roller.

APPLICATION RATE: 0.25 - 1 gallon per 100 sq. ft. depending on porosity of surface and method of application. Work material to a smooth and even consistency. Avoid excessive build up or puddles of primer. DO NOT APPLY TO ASPHALT DRIVEWAYS.

SPRAY INFO: 100-500 PSI, .019-.031 Tip Size, 0.5 - 2.0 GPM

PRECAUTIONS: When transporting this product, ensure that lid is tight and pail secure and upright. Do not allow pail to tumble as this may cause lid to loosen and leakage to occur. Do not transport on passenger seats or inside the passenger compartment of any vehicle. Store product in the cargo area of vehicle, and secure over protective cloths to prevent damage due to accidental spills. Do not store at temperatures above 110° F. This manufacturer also disclaims liability for flat surface application where poor drainage or moisture may prevail. Do not reuse empty containers. Do not use in drinking water or food systems.

CLEAN-UP: Clean tools with paint thinner or mineral spirits.

TYPICAL PHYSICAL & PERFORMANCE CHARACTERISTICS

Weight Per Gallon	7.4-7.9 lbs.
Residue by Evaporation, %	60 min.
Consistency	Brush or Spray
Tack Time (50% Relative Humidity, 70°F)minutes	
Full Cure (50% Relative Humidity, 70°F)48 hours	
Application Temperatures	35° - 120°F
Clean-up Tools	Paint Thinner, Mineral Spirits

Approx. Shipping Weights: (Note: All approx. weights include container.)

1 gallon (3.4 L)	8 lbs.
5 gallons (18.9L)	40 lbs.
55 drums (208.2L)	460 lbs.

CAUTION – COMBUSTIBLE MIXTURE CAUTION!: HARMFUL OR FATAL IF SWALLOWED. EYE, SKIN AND RESPIRATORY IRRITANT.

Contains Petroleum Distillate. Keep away from heat, sparks and open flame. If swallowed DO NOT induce vomiting. Call physician immediately. In case of : Eye contact - flush with large amounts of room temperature water for 15 minutes; Skin contact - wash thoroughly with soap and water; Irregular or stopped breathing - administer oxygen, give artificial respiration and get medical attention immediately. Avoid prolonged breathing of vapor or spray mist.

FOR EXTERIOR USE ONLY
Use with adequate Ventilation
Keep Out of Reach of Children
Product shipped within California
VOC < 350 g/L (less water + exempt)
Do not need 400 g/L for shipped out
because Tacoma formulation finally fixed.

CALIF. PROP. 65 • CHEMICAL WARNING (CALIFORNIA HEALTH AND SAFETY CODE #25249.5 ET SEQ). WARNING: This product contains chemicals known to the State of California to cause cancer, birth defects or reproductive harm. Use proper protection and adequate ventilation, when using product.

WARRANTY AND DISCLAIMER: To the best of our knowledge, the technical data contained herein is true and accurate at the date of issuance and is subject to change without prior notice. User must contact APOC to verify correctness before specifying or ordering. No guarantee of accuracy is given or implied. Liability, if any, is limited to replacement of product unless installed by an approved contractor in accordance with APOC warranty procedures and program.

For limited warranty and disclaimer information, visit our website at:
www.apoc.com/productwarrantyinfo.

©2010 Gardner Asphalt Corporation Manufactured
by / Fabricado por: Gardner Asphalt Corporation
P.O. Box 5449, Tampa, FL 33675



See MSDS for more info



Gardner Asphalt Corporation • P.O. Box 5449 • Tampa, Florida 33675-5449
Phone: (813) 248-2101 • Fax (813) 248-6768 • www.apoc.com