29 Perfectseal Quick-Grip Modified Bitumen Adhesive

DESCRIPTION:

Karnak 29 Perfectseal Quick-Grip Modified Adhesive Brush Grade is a multipurpose, SBS polymer modified bitumen, cold-process adhesive. This economical and useful adhesive is designed to provide greater bonding strength.

USES:

Trowel Grade:

Designed as an adhesive for SBS modified bitumen single-ply membranes. Flashing vertical surfaces, skylights, vents and pipes (Not for use around heated vents or pipes).

Brush Grade:

Designed as an adhesive for SBS modified bitumen single-ply membranes. Also may be used to adhere conventional roll roofing membranes and granular cap sheets.

APPLICATION:

Trowel Grade:

Surface must be dry, clean and free of oil, grease, dust, dirt and all materials that might interfere with the adhesive bond. Apply Karnak 29 Perfectseal Quick-Grip Trow el Grade on surfaces at a 1/8" thickness, as determined by the irregularity and absorptive nature of the surface. Excessive use may create blistering. A 1/4" serrated trowel is the recommended application tool. Overlaps should be at least 4" wide. Allow an open time of 15-20 minutes before placing membrane into adhesive.

Brush Grade:

Surface must be dry, clean and free of oil, grease, dust, dirt and all materials that might interfere with the adhesive bond. Apply Karnak 29 Perfectseal Quick-Grip Brush Grade at the rate of 1 to 2 gallons per 100 sq.ft. on horizontal surfaces, as determined by the irregularity and absorptive nature of the surface. Excessive use may create blistering. A rubber squeegee, brush or roller is the recommended application tool. Overlaps should be at least 4" wide. Allow an open time of 15-20 minutes before placing membrane into adhesive

CAUTION: Combustible Mixture. Do not use near fire or flame. KEEP OUT OF REACH OF CHILDREN. Do not thin.

CARE OF TOOLS:

Equipment may be thoroughly cleaned after use with Karna-Klean or mineral spirits, taking necessary precautions when handling combustible materials.





29 Perfectseal Quick-Grip Modified Bitumen Adhesive

WARNING: Keep away from open flame. Keep container closed when not in use. Avoid prolonged or repeated contact with skin or eyes. IF splashed in eyes, flush immediately with copious quantities of running water. Do not take internally. If swallowed, do not induce vomiting; call a physician immediately. Use with adequate ventilation. Provide adequate ventilation in confined areas during application. Vapors can cause headaches, nausea, dizziness and irritation of the respiratory tract, or unconsciousness. Wash exposed areas promptly and thoroughly after skin contact and before eating, drinking or using tobacco products. Prior to using this product it is necessary to read and understand the MSDS which is available from your employer or by calling the Karnak Technical Sales office at 1-800-526-4236. Dispose of in an environmentally safe manner. Cover air intakes during application and while drying.

Please see page 222 for additional mold and safety information.

WEB: http://www.karnakcorp.com



